


PROD REV: A-1 DWG VER: V-1

PATIO TABLE

(PTBL-000-000)





Contents

VARNING	3
SILL OF MATERIALS	4
GLOSSARY	5
AWS SYMBOLS	6
ASSEMBLY INSTRUCTIONS	7
PART DRAWINGS	. 19



WARNING



SAFETY WARNING: WELDING INVOLVED

Before you begin the assembly process, it's crucial to understand the risks and necessary precautions associated with welding. Please read and adhere to the following safety guidelines:

- **Professional Supervision:** If you're inexperienced in welding, consider seeking guidance or supervision from a trained professional. A small error can have significant consequences on the durability and safety of your furniture.
- **Protective Gear:** Welding can produce intense UV light, sparks, and spatter. Always use a welding helmet with the correct shade of lens, wear flame-resistant clothing, leather gloves, and safety boots. Safety glasses should be worn underneath the helmet for added eye protection.
- Work in a Safe Environment: Welding can produce harmful fumes and gases. Always work in a well-ventilated space, preferably outdoors. Remove any flammable materials from the vicinity, and always have a fire extinguisher on hand.
- **Pre-welding Inspection:** Thoroughly inspect the metal parts for any signs of damage, rust, or contamination. Clean the areas to be welded to ensure there are no oils, paints, or other materials that might interfere with the weld.
- **Equipment Check:** Before you start, ensure your welding machine is in proper working condition. Check cables, connectors, and welding gun for any damage or wear.
- Avoid Water: Never weld in wet conditions or touch the welding equipment with wet hands or gloves. Water is a conductor of electricity and can increase the risk of shocks.
- **Grounding:** Ensure that the piece you're welding is correctly grounded. A proper ground connection is essential for safety and for producing quality welds.
- **Post-welding Protocol:** Once you finish welding, let the welded parts cool down gradually. Rapid cooling can lead to metal warpage or structural weaknesses.
- **Stay Informed:** Familiarize yourself with the Material Safety Data Sheet (MSDS) for the metals you're working with and the filler materials you're using.
- **First Aid:** Keep a first aid kit nearby. In case of minor burns, immediately hold the affected area under cold running water for at least 10 minutes.
- Limit Distractions: Ensure that your workspace is free from unnecessary distractions. Focus is critical when welding to maintain consistent quality and safety.
- Store Equipment Safely: After completion, store your welding equipment in a dry, safe place away from children's reach.

Remember, your safety and the quality of your work go hand in hand. Always prioritize safety precautions and never rush the welding process. If you're ever uncertain about a step or safety measure, seek guidance before proceeding.

Your safety is our top priority! No task justifies risking injury.



BILL OF MATERIALS

See page 19 for detailed drawings of each part.

ITEM	PART NUMBER	DESCRIPTION		MATERIAL	QTY.
1	1000-050-004	Phillips Flat Head Wood Screws - #10-13 x 1"		STEEL	24
2	PTBL-050-000	TUBE MEMBER - FRONT		RT_A500_3x1_0.075T	2
3	PTBL-051-000	SUPPORT MEMBER	A-1	SQ_A500_1.5x1.5_0.065T	1
4	PTBL-053-000	SIDE TUBE - BOTTOM	A-1	RT_A500_3x1_0.075T	2
5	PTBL-053-001	SIDE TUBE - SHORT LEFT	A-1	RT_A500_3x1_0.075T	2
6	PTBL-053-002	SIDE TUBE - SHORT RIGHT	A-1	RT_A500_3x1_0.075T	2
7	PTBL-053-003	SIDE TUBE - TOP	A-1	RT_A500_3x1_0.075T	2
8	PTBL-054-000	SLAB SUPPORT	A-1	SM_A36_0.01345T	2
9	PTBL-900-000**	WOOD PLANK	A-1	2X4 WOOD	6

**** ITEMS NOT PROVIDED**

GLOSSARY

METAL TUBE

SQ A500 2X2 0.065T MATERIAL SIZE

TYPE

MATERIAL **THICKNESS**

SHEET METAL

SM A36 0.065T

TYPE

MATERIAL

MATERIAL **THICKNESS**

Type

SQ = Square tube profile RT = Rectangle tube profile RD = Circle tube profile AG = Angle tube profile SM = Sheet Metal

Material Thickness


10ga - 0.1345" 12ga - 0.1035" 14ga - 0.075" 16ga - 0.065"

AWS SYMBOLS

The following are some of the common weld symbols you will encounter when reading our assembly instructions.

AWS SYMBOL	NAME	DESCRIPTION		
\square	FILLET WELD	Triangular weld joining two surfaces at right angles; common in T-joints and lap joints.		
\ominus	SEAM WELD	Joins metal using a hole in the top piece, fusing with the bottom piece.		
0	SPOT WELD	Used for fusing overlapping metals at discrete poi often used in sheet metal fabrication.		
	PLUG WELD	Process creating a consistent weld along overlapp materials; suitable for containers and cylindrical assemblies.		

WELD INDICATION	DESCRIPTION	
1/8 / 1/8 - 6	TACK WELD (Small and temporary weld that hold parts together ready for final welding.)	
1/4 1.5 - 6	FULLY WELD (Last welding operation performed to complete a joint or structure, ensuring its integrity.)	




This symbol tells us to make a 1/8" high Fillet Weld, 1/8" long (a "tack"), and to do so along the seam every 6" (the pitch).





PROD REV: A-1 DWG VER: V-1

ASSEMBLY INSTRUCTIONS




2







-PTBL-053-001 1/8 / 1/8





NOTES:

REPEAT STEPS 1 THRU 4 FOR OTHER SET OF LEGS











10



11



NOTES:

NOW IS THE PERFECT TIME TO GO BACK AND FINISH WELDING ALL THE PREVIOUS TACK WELDS


WE RECOMMEND A 0.25" HIGH FILLET WELD, 1.5" LONG


12 PTBL-900-000-L S





PROD REV: A-1 DWG VER: V-1


PART DRAWINGS














		sions			
REV.	DESCRIPTION	DATE	APPROVED		
<u>REV.</u>	DESCRIPTION	DATE	APPROVED		
			- 21.88	2.00	
				DIMENSIONS ARE IN	INCHES, UNLESS SPECIFIED OTHERWI
WELD PROJECTS		DIMENSIONS ARE IN PART # PTBL-054-000	INCHES, UNLESS SPECIFIED OTHERWIS MATERIAL SM_A36_0.1345T		
101 INDUSTRIAL CT, CONROE, TX 77301 PH: 281-238-9652 PROPRIETARY AND CONFIDENTIAL : THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF WELD PROJECTS. ANY REPRODUCTION, IN PART OR AS A				5	
PROPRIETAR	Y AND CONFIDENTIAL :	THE INFORMATION C	ONTAINED IN THIS DRAWIN		

